

Spare Parts Catalog 2 HL 270 Material number: 4143.020.164 Current date: 23.09.2021

ZF Friedrichshafen AG Hauptverwaltung 80038 Friedrichshafen Deutschland Telefon: +49 7541 77-0 Telefax: +49 7541 77-908000 zuständiges Werk: www.zf.com Passau

Notes relating to the spare parts catalog

Setup of the spare parts catalog

- Cover sheet

- Tecnical Cover (only in SDM print)

Overview of figures

- Figure

- Associated parts list

- Next figure
- Associated parts list
- ...

Overview of figures

Bildtafel Figure	Sachnummer Product number	Benennung (Description)	Technische Info Technical info	Description (Benennung)	Menge Quantity	Einheit Unit
068.08.17	1316.170.001	AUSLEGER	WL	SHIFT TURRET	1	Stk
068.08.06	1316.170.031	DECKEL	WL*H-H *VM	COVER	1	Stk
0680814	1316.170.808	DECKEL	WL*AUSL+GEH*H-H*HF160N	COVER	1	Stk
08	1316.170.441	ANSCHLUSSTEILE	WL*NG-VORB*RG-SCHL*168N *BAJONETT	CONNECTING PARTS	1	Stk

The "gap" indicates that there is no separate graphics panel (poster) for this assembly The parts of this assembly are shown with the same mid-section number on the figure

Figure and parts list

2 01.630 * 01.600 01.310 01.310 01.310 01.350 * 01.350 * 01.360 01.360

1 Positions and subpositions

Pos.	Sachnummer Product number	Benennung (Description)		Description (Benennung)	Menge Quantity	Einheit Unit
0370	1315.201.054	RUECKLAUFBOLZEN	KPL.16S151*SG*L= 79	REV.IDLER SHAFT	1	Stk
/0120	0631.329.293	SPANNSTIFT		SLOT. PIN	1	Stk

Positions marked with "/" are the individual items of a completion

For example: Position 0370 contains a centering pin with the position /0120

(2) <u>Combinations with standardized parts</u>

	Sachnummer Product number	Benennung (Description)	Technische Info Technical info	Description (Benennung)	Menge Quantity	Einheit Unit
0630		VERSCHL.SCHR.		SCREW PLUG	1	Stk
	0636.302.067	VERSCHL.SCHR.		SCREW PLUG	1	Stk
	0634.801.249	DICHTRING	A 26 X 31	SEALING RING	1	Stk

The parts list shows the components included in the combination of standardized parts

3 Depiction of position/item number on the figure and in the parts list

01.620 - on the figure 01 relates to the assembly in which the position is included. Due to program-related reasons, it is shown on the figure.

0620 - in the parts list

Pos	Sachnummer	Benennung	Technische Info	Description	Menge	Einheit
	Product number	(Description)	Technical info	(Benennung)	Quantity	Unit
062	0732.040.736	DRUCKFEDER		COMPRESSION SPRING	1	Stk

4 <u>*-Positions</u>

Positions marked with an * are optional i.e. inclusion in the parts list is not mandatory. The following note is shown on the figure

*	suivant la nomenciature
	secondo la distina base

(5) Parts, dotted display

Parts with dotted display on the figure are only used for orientation of other parts



Material number: 4143.020.164



Pos.	Information	Amendment number
	CUSTOMER-VEHICLE DATA 1:	
	CUSTOMER: TVEX	
	VEHICLE DESIGNATION: EK-20	
	ENGINE POWER: 114,0 KW	
	WEIGHT EMPTY: 20,000 TO	
	TIRES: 10.00-20	
	TIRE RADIUS: 0,506 M	
	HYDRAULIC PUMP: A8VLAH	
	MANUFACTURER: REXROTH	
	HYDR. PUMP POWER: 88,8 KW	
	OIL FLOW: 200,0 CDM	
	HYDROMOTOR: A6VM 140	
	MANUFACTURER: REXROTH	
	DIFFERENTIAL PRESSURE: 320 BAR	
	FRONT AXLE: MS-E 3060	
	REAR AXLE: MT-E 3060	
	AXLE RATIO: 18,66	
	PERFORMANCE CALC.: 4143 701 599	
	BRAKE CALCULATION: 4143 709 384	
	VEHICLE DESIGNATION: EK 18-90 SCRAP	
	ENGINE POWER: 90,0 KW	
	WEIGHT EMPTY: 21,400 TO	
	TIRES: 10.00-20	
	TIRE RADIUS: 0,506 M	
	HYDRAULIC PUMP: A11VO 130	
	MANUFACTURER: REXROTH	
	HYDR. PUMP POWER: 63,6 KW	
	OIL FLOW: 210,2 CDM	
	HYDROMOTOR: A6VM 140	
	MANUFACTURER: REXROTH	
	DIFFERENTIAL PRESSURE: 320 BAR	
	FRONT AXLE: MS-E 3070	
	REAR AXLE: MT-E 3070	

Material number: 4143.020.164



AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 652 BRAKE CALCULATION: 4143 709 384 VEHICLE DESIGNATION: TVEX 180 1 ENGINE POWER: 90,0 KW WEIGHT EMPTY: 21,400 TO TIRES: 10.00-20 TIRE RADIUS: 0,506 M HYDRAULIC PUMP: A11V0 130 MANUFACTURER: REXROTH HYDR. PUMP POWER: 63,6 KW OIL FLOW: 210,2 CDM HYDROMOTOR: A6VM 150 MANUFACTURER: REXROTH DIFFERENTIAL PRESSURE: 320 BAR FRONT AXLE: MS-E 3070 REAR AXLE: MT-E 3070 REAR AXLE: MT-E 3070 AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: 2F- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM TRANSMISSION INSTALLATION: REMOTE MOUNT	ber
BRAKE CALCULATION: 4143 709 384 VEHICLE DESIGNATION: TVEX 180 I ENGINE POWER: 90,0 KW WEIGHT EMPTY: 21,400 TO TIRES: 10.00-20 TIRE RADIUS: 0,506 M HYDRAULIC PUMP: A11VO 130 MANUFACTURER: REXROTH HYDR. PUMP POWER: 63,6 KW OIL FLOW: 210,2 CDM HYDROMOTOR: A6VM 150 MANUFACTURER: REXROTH DIFFERENTIAL PRESSURE: 320 BAR FRONT AXLE: MS-E 3070 REAR AXLE: MS-E 3070 AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
VEHICLE DESIGNATION: TVEX 180 IENGINE POWER: 90,0 KWWEIGHT EMPTY: 21,400 TOTIRES: 10.00-20TIRE RADIUS: 0,506 MHYDRAULIC PUMP: A11VO 130MANUFACTURER: REXROTHHYDR. PUMP POWER: 63,6 KWOIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070REAR AXLE: MT-E 3070REAR AXLE: MT-E 3070BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
ENGINE POWER: 90,0 KWWEIGHT EMPTY: 21,400 TOTIRES: 10.00-20TIRE RADIUS: 0,506 MHYDRAULIC PUMP: A11VO 130MANUFACTURER: REXROTHHYDR. PUMP POWER: 63,6 KWOIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
WEIGHT EMPTY: 21,400 TO TIRES: 10.00-20 TIRE RADIUS: 0,506 M HYDRAULIC PUMP: A11VO 130 MANUFACTURER: REXROTH HYDR. PUMP POWER: 63,6 KW OIL FLOW: 210,2 CDM HYDROMOTOR: A6VM 150 MANUFACTURER: REXROTH DIFFERENTIAL PRESSURE: 320 BAR FRONT AXLE: MS-E 3070 REAR AXLE: MT-E 3070 AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
TIRES: 10.00-20 TIRE RADIUS: 0,506 M HYDRAULIC PUMP: A11VO 130 MANUFACTURER: REXROTH HYDR. PUMP POWER: 63,6 KW OIL FLOW: 210,2 CDM HYDROMOTOR: A6VM 150 MANUFACTURER: REXROTH DIFFERENTIAL PRESSURE: 320 BAR FRONT AXLE: MS-E 3070 REAR AXLE: MS-E 3070 REAR AXLE: MT-E 3070 AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
TIRE RADIUS: 0,506 MHYDRAULIC PUMP: A11VO 130MANUFACTURER: REXROTHHYDR. PUMP POWER: 63,6 KWOIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: 2F- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
HYDRAULIC PUMP: A11VO 130MANUFACTURER: REXROTHHYDR. PUMP POWER: 63,6 KWOIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
MANUFACTURER: REXROTHHYDR. PUMP POWER: 63,6 KWOIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
HYDR. PUMP POWER: 63,6 KWOIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
OIL FLOW: 210,2 CDMHYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
HYDROMOTOR: A6VM 150MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
MANUFACTURER: REXROTHDIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
DIFFERENTIAL PRESSURE: 320 BARFRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
FRONT AXLE: MS-E 3070REAR AXLE: MT-E 3070AXLE RATIO: 18,66PERFORMANCE CALC.: 4143 701 772BRAKE CALCULATION: 4143 709 512PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HLTRANSMISSION TYPE: 2 HL 270DROP CENTER DISTANCE: 185 MM	
REAR AXLE: MT-E 3070 AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM DROP	
AXLE RATIO: 18,66 PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
PERFORMANCE CALC.: 4143 701 772 BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
BRAKE CALCULATION: 4143 709 512 PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
PRODUCT DESCRIPTION: ZF- POWERSHIFT TRANSMISSION HL TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
TRANSMISSION TYPE: 2 HL 270 DROP CENTER DISTANCE: 185 MM	
DROP CENTER DISTANCE: 185 MM	
TRANSMISSION INSTALLATION: REMOTE MOUNT	
INSTALLATION POSITION: HORIZONTAL	
OUTPUT FLANGE: DIN 120	
GEAR RATIO: 1ST GEAR=4,869; 2ND GEAR=1,196	
HYDRO MOTOR SPLINE: N45 X 2 X 30 X 21 X 10H	
CENTERING DIAMETER: 180 H7	
VALVE BLOCK: SEPARATELY	
VOLTAGE: 24 VOLT	
DOWNSHIFT PROT.: HYDR. CONNECTION M18X1.5	
SPEED SENSOR: WITHOUT	

Technical Cover Page 3 from 3

Material number: 4143.020.164



Pos.	Information	Amendment number
	OIL FILLING: WITH	
	GEARBOX OIL - GRADE: TE ML 07	
	OIL FILL QUANTITY CA: 2,90 L	
	TYPE PLATE: ZF- STANDARD	
	PAINTING: PRIMING	
	COLOR: BLACK RAL 9005	
	SEPARATE ORDER CUSTOMER: 0750.132.135 VALVE BLOCK: 24V	
	DOCUMENTATION:	
	SECTION DRAWING: 4143 020 031	
	INSTALLATION DRAWING: 4143.620.020	
	INSTALL. INSTRUCTIONS: 5872 014 002	

Assembly group overview Page 1 from 1

Material number: 4143.020.164



Graphics	Pos.	Material number	Name	Quantit y	Amend. no.	Techn. Info.
4143125044 20	490	4143.125.044	INPUT HOUSING	1		
4143101043 00	10	4143.101.043	HOUSING	1		
4143151019 00	810	4143.151.019	MULTIDISK BRAKE	1		
4143152011 00	830	4143.152.011	COUPLING	1		
4143115017 00	290	4143.115.017	PLANETARY DRIVE	1		
4143115401 00	300	4143.115.401	PLANETARY DRIVE	1		
4143115405 00	295	4143.115.405	PLANETARY DRIVE	1		
4143103037 20	50	4143.103.037	OUTPUT	1		
4143103420 50	57	4143.103.420	OUTPUT	2		
4143142025 20	520	4143.142.025	GEAR SHIFT SENSOR	1		
4143142406 20	540	4143.142.406	GEAR SHIFT SENSOR	1		
4143142407 20	525	4143.142.407	GEAR SHIFT SENSOR	1		
4143121011 20	390	4143.121.011	OIL PIPE	1		
4143139001 00	900	4143.139.001	TYPE PLATE	1		

Plant Page 1 from 1

Material number: 4143.020.164 Plant: 414312504420 Material-assembly-group-no: 4143.125.044




(1000)

Page 1 from 2

Material number: 4143.020.164 Plant: 414310104300 Material-assembly-group-no: 4143.101.043






Plant Page 2 from 2

Material number: 4143.020.164 Plant: 414310104320 Material-assembly-group-no: 4143.101.043






Plant Page 1 from 2

Material number: 4143.020.164 Plant: 414315101900 Material-assembly-group-no: 4143.151.019






Plant Page 2 from 2

Material number: 4143.020.164 Plant: 414315101930 Material-assembly-group-no: 4143.151.019






Plant Page 1 from 1

Material number: 4143.020.164 Plant: 414315201100 Material-assembly-group-no: 4143.152.011






Page 1 from 1

Material number: 4143.020.164 Plant: 414311501700 Material-assembly-group-no: 4143.115.017






Page 1 from 1

Material number: 4143.020.164 Plant: 414311540100 Material-assembly-group-no: 4143.115.401





Page 1 from 1


Material number: 4143.020.164 Plant: 414311540500 Material-assembly-group-no: 4143.115.405



Plant Page 1 from 1

Material number: 4143.020.164 Plant: 414310303720 Material-assembly-group-no: 4143.103.037






Page 1 from 1

Material number: 4143.020.164 Plant: 414310342050 Material-assembly-group-no: 4143.103.420






Page 1 from 1

Material number: 4143.020.164 Plant: 414314202520 Material-assembly-group-no: 4143.142.025






Page 1 from 1

Material number: 4143.020.164 Plant: 414314240620 Material-assembly-group-no: 4143.142.406






Page 1 from 1

Material number: 4143.020.164 Plant: 414314240720 Material-assembly-group-no: 4143.142.407






Page 1 from 1

Material number: 4143.020.164 Plant: 414312101120 Material-assembly-group-no: 4143.121.011





Page 1 from 1

Material number: 4143.020.164 Plant: 414313900100 Material-assembly-group-no: 4143.139.001



